

WATER PROOFING COMPOUND – WP 999

DESCRIPTION

GEETA WP-999 is a unique **Polymer modified Elastomeric** waterproofing powder made with the best quality of German Polymers. It is Cementitious, dry powder, having properties of High Flexible waterproof coating with Water Vapor Permeability.

Salient Features :

- Makes building component totally waterproof
- Excellent adhesion on the concrete.
- Good water vapor permeability (i.e. Breathable)
- Highly flexible having crack bridging property.
- Resist Extreme hydrostatic pressure.
- UV Light & Alkalies stable.
- Easy Application by Brush.
- Resists Fungus.

Applications :

Terraces, Water tanks, Bath rooms & Toilets, Swimming Pools, Podiums, Flowerbeds, Sloping Roofs etc.

Note : Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on application methods and site conditions.

INSTRUCTIONS

Substrate preparation

Remove all dust, oil and debris. Dampen the dry concrete surface before application of **GEETA WP-999**.

Application

Take 1 kg of **GEETA WP-999** and add 1 kg of clean water. Mix the solution completely. Apply this coat as Primer on the surface. Allow it to dry.

Now take 2 kg of **GEETA WP-999** and add 1 kg of clean water. Mix the solution completely. Apply this coat with brush on the primed surface. Allow it to dry.

Repeat the above coat as a third & final coat on the surface. Allow it to dry.

Curing

Natural curing in ambient temperature should be allowed.

Coverage

It covers approximately 10 Sq. Ft area in 1 Kg of **GEETA WP-999** for 3 coats application

PRECAUTIONS

GEETA WP-999 is non-hazardous. However, care should be taken when handling it. Avoid contact with skin, eyes and mouth. In case of eye splashes or excessive skin contact, wash thoroughly with clean water. If irritation persists, seek immediate medical attention.

PACKAGING

25 kg bag

SHELF LIFE

Up to 6 months from the date of manufacture

DISCLAIMER:

The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with our instructions. The information contained herein is to the best of our knowledge, true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application.

Office No 1, Bldg. No. D 9, Popular Nagar, Warje, On Mumbai Bangalore Highway, Pune 411058.

Phone : 020 – 25232607 / 8888867522 Email : info@gscpl.in / sarvesh@gscpl.co.in

Website : www.gscpl.co.in OR www.blastingpainting.com